

## DECLARATION OF PERFORMANCE

No. 046-01-CPR-2013-06-27

1. Unique identification code of the product-type:

**Product elastomeric  
modified reinforced bitumen sheet Bikroelast EPP**

2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4):

**Bikroelast EPP**

Size	Protective coating	Product number
1×15 m	Film-film	001710

3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

**Designed for installation as the bottom layer of roof cladding on buildings and constructions for waterproofing of engineering structures. Used for new roofing construction and for repair of old roof. Ideal for the installation as two-layer waterproofing for the foundations according to EN 13969. Not recommended to use as one-layer roofing cladding or one-layer waterproofing. Can be used as underlayer for a bitumen shingles with mechanical fastening.**

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):

**TechnoNicol-Vyborg Ltd.,  
Ruberoïdnaya St., 7, Leningradskaya region, Vyborg, 188804, RUSSIA  
Tel. +78137839072  
Fax. +78137839091  
Email: [Main@vbg.tn.ru](mailto:Main@vbg.tn.ru)**

5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):

**TechnoNicol-Construction systems LLC,  
Gilyarovskogo St., 47/5, Moscow 129110, RUSSIA  
Tel. +74959255575  
Fax. +74959805249  
Email: [europa@tn.ru](mailto:europa@tn.ru)  
Website: [www.tn-europe.com](http://www.tn-europe.com)**

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in CPR, Annex V:

**System 2+**

7. In case of the declaration of performance concerning a construction product covered by a harmonised standard:

**Notified certification body No. 0809 - VTT Expert Services Ltd. performed the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment and evaluation of factory production control and issued the certificate of conformity of the factory production control.**

**This certificate No. 0809 CPD-0560 was first issued on August 20.2006  
updated on June 27.2013  
Certificate 0809-CPD-0805 June 27.2013**

## 9.Declared performance

### Bikroelast EPP

№		The indicator name	Test method	Unit of measure	Norm	Harmonised technical specification
<b>Полиэстр / Polyester, 150 g/m<sup>2</sup></b>						
1		Защита верхней стороны	Protection of the top side			film
2		Защита нижней стороны	Protection of the bottom side			film
3	MLV	Длина	Rolls length,	EN 1848-1	mm	≥10000
4	MLV	Ширина	Rolls width	EN 1848-1	mm	≥1000
5	Pass	Прямолнейность	Straightness	EN 1848-1	mm	Pass
6	MDV	Масса на единицу площади	Mass per unit area	EN 1849-1	kg/m <sup>2</sup>	3.0-0.15
7	MDV	Толщина	Thickness	EN 1849-1	mm	2.5 ±0.1
8		Видимые дефекты	Visible defects	EN 1850-1	-	Visible defects
9	MLV	Гибкость в холодном состоянии	Cold flexibility, -10 °/ø 30 mm- upper face and lower face	EN 1109-1	°C	≤-10/30
10	MLV	Испытание на теплостойкость	Flow resistance at elevated temperature +85 °C/2 h - upper face and lower face	EN 1110	°C	≥85
11	MDV	Сцепление посыпки с покровным слоем	Adhesion of granules	EN 12039	%	-
12	MDV	Относительное удлинение	Elongation, L/T	EN 12311-1	%	50/50 ±25
13	MDV	Разрывные показатели	Tensile strength, L/T	EN 12311-1	N/50mm	600/500 ±100
14	MLV	Стабильность размеров	Dimensional stability, +80 °C/24 h, L, method B	EN 1107-1	%	≤±0,6
15	MDV	Сопротивления на распространение трещин (при помощи штифта)	Nail shank tear resistance, L/T	EN 12310-1	N	180/180 ±50
16	Pass	Водонепроницаемость	Watertightness	EN 1928	kPa	200
17	MDV	Сопротивление отслаивания на стыках	Peel resistance of joints, A/M	EN 12316-1	N/50mm	80/100±50
18	MDV	Сопротивление соединений на разрыв	Shear resistance of joints	EN 12317-1	N/50mm	450±50
19	MLV	Сопротивление удару при +23 °C	Resistance to impact-impact resistance at +23 °C/ø12.7 mm (500 g/h.mm), method B	EN 12691	mm	h≥800
20	MLV	Сопротивление удару при +23 °C	Resistance to impact-impact resistance at +23 °C/ø12.7 mm (500 g/h.mm), method A	EN 12691	mm	h≥500
21	MLV	Сопротивление статическому нагружению, метод А	Resistance to static loading, 200 N (20 kg) Method A (EPS support)	EN 12730	kg	≥ 20
22		Пожарные испытания	External fire exposure	EN 13501-5 ENV		B <sub>ROOF</sub> (t2)
23		Паропроницаемость	Determination of water vapor transmission properties	EN 1931	—	μ=20000
<b>Properties after artificial ageing/ EN 1296. 12 weeks at +70 °C</b>						
24	MDV	Теплостойкость	Flow resistance at elevated temperature +80 °C/2 h - upper face and lower face	EN 1110	°C	≥80
25	MDV	Гибкость в холодном состоянии	Cold flexibility, -5 °/ø 30 mm- upper face and lower face	EN 1109-1	°C	≤-5/30
26	MDV	Водонепроницаемость	Watertightness	EN 1928	kPa	≥200
<b>Dangerous substances:</b>						

Does not include dangerous substances.

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

General director

Savenkov V.V.

01.07.2013  
(place and date of issue)

(name and function)

(signature)